

# Comprehensive Finished Street Name Signs Checklist

## Easy Order Checklist:

### 1 Select Blade

- Flat Blade .080" Aluminum
- Extruded Blade NO RADIUS  
6" and 9" Blade Heights Only
- Econo Vandal Resistant  
3MM ACM MATERIAL - NO SCRAP VALUE  
6", 8" and 9" Blade Heights Only

Custom Dr

### 2 Reflective Type

- High Intensity Prismatic
- DG<sup>3</sup> MUTCD guidance - For ground and overhead mounted signage: White reflective must be > 120 candlepower, Green must be > 7.

### 3 Color Scheme

- White on Green
- White on Blue
- White on Brown
- Black on White
- White on Black
- Other/Custom

Custom Dr

Custom Dr

Custom Dr

Custom Dr

Custom Dr

MUTCD guidance - Acceptable alternative background colors to Green are Blue, Brown or White. The legend shall be White, except for Black on White signs. Custom colors require adequate contrast, call a customer service specialist for guidance.

### 4 Sides

- Double Face Ground Mount
- Single Face Overhead Mount

### 5 Border

- None MUTCD guidance - Borders are optional, but if used, must be the same color as the letters.
- Edge - Should use on dark backgrounds
- Inset - Should use on white backgrounds

### 6 a. Logo or Route Symbol

- None MUTCD guidance - Route symbols or Logos may be placed on the left side of a sign.
- Yes The maximum height is the same as the letter height.

### 6 b. Prefix/Suffix

- Full Size MUTCD Guidance - Prefix/Suffix Height may be smaller than the height of the primary copy and may be abbreviated. No punctuation is to be used.
- Half Size

### 7 Vandal Resistant Hole Punch

- None
- VPA 12 Bolt thru
- Other

## Roadway Type Local Two Lane Roads 0-25 MPH

MUTCD guidance - Initial upper-case letters at least 4" high and lower-case letters 3/4 height of upper-case.

### 8 Dimensions



Blade Height: 6" | Corner Radius .75"  
Letter Height/Prefix: 4" | Suffix Height: 2"  
Font: Highway Gothic B | Case: U/L

Custom Dr



Blade Height: 8" | Corner Radius .75"  
Letter Height/Prefix: 4" | Suffix Height: 2"  
Font: Highway Gothic B | Case: U/L

## Two Lane Roads Over 25 MPH and Multi Lane Roads 0-40 MPH

MUTCD guidance - Initial upper-case letters at least 6" high and lower-case letters 3/4 height of upper-case.



Blade Height: 9" | Corner Radius .75"  
Letter Height/Prefix: 6" | Suffix Height: 3"  
Font: Highway Gothic B | Case: U/L



Blade Height: 12" | Corner Radius 1.5"  
Letter Height/Prefix: 6" | Suffix Height: 3"  
Font: Highway Gothic B | Case: U/L

## Multi Lane Roads Over 40 MPH

MUTCD guidance - Initial upper-case letters at least 8" high and lower-case letters 3/4 height of upper-case.



Blade Height: 12" | Corner Radius 1.5"  
Letter Height/Prefix: 8" | Suffix Height: 4"  
Font: Highway Gothic B | Case: U/L

## Overhead Mast Arm

MUTCD guidance - Initial upper-case letters at least 12" high and lower-case letters 3/4 height of upper-case.



Blade Height: 18" | Corner Radius 1.5"  
Letter Height/Prefix: 8" | Suffix Height: 8"  
Font: Highway Gothic C | Case: U/L



Blade Height: 18" | Corner Radius 1.5"  
Letter Height: 8" | Prefix/Suffix Height: 4"  
Font: Highway Gothic C | Case: U/L



Blade Height: 24" | Corner Radius 1.5"  
Letter Height/Prefix/Suffix Height: 12"  
Font: Highway Gothic C | Case: U/L



Blade Height: 24" | Corner Radius 1.5"  
Letter Height/Prefix: 12" | Suffix Height: 6"  
Logo/Route Symbol Height: 12"  
Font: Highway Gothic C | Case: U/L

**Street Name Signs MUST be Type II copy on Type I background or better.**

We recommend using **3M** High Intensity Prismatic for **Ground Mounted SNS** and **3M** Diamond Grade Cubed for **Overhead Mounted SNS**

**IMPORTANT NOTE:** Please e-mail or fax your list of signs (MUST BE A TYPED LIST), along with the specifications you've selected above for a personalized quote. Prefixes/Suffixes MUST use MUTCD Abbreviation, No Punctuation, Special Characters or Block Numbers allowed. Street Name Signs are Priced based on Length.

**3M** Certified Sign Fabricator



VOICE: 1-800-367-1492 • FAX: 1-800-206-3444

sales@cpcsigns.com • www.cpcsigns.com