

# Street Name Signs Checklist

## Easy Order Checklist:

### 1 Select Blade

- Flat Blade .080" Aluminum
- Extruded Blade NO RADIUS  
6" and 9" Blade Heights Only
- Econo Vandal Resistant  
3MM ACM MATERIAL - NO SCRAP VALUE  
6", 8" and 9" Blade Heights Only

### 2 Reflective Type

- High Intensity Prismatic
- VIP MUTCD guidance - For ground and overhead mounted signage, White reflective must be  $\geq 120$  candlepower. Green must be  $\geq 7$ .
- DG<sup>3</sup>
- E - Non-Compliant Reflective

### 3 Color Scheme

- White on Green
- White on Blue
- White on Brown
- Black on White
- Other/Custom

MUTCD guidance - Acceptable alternative background colors to Green are Blue, Brown or White. The legend shall be White, except for Black on White signs. Custom colors require adequate contrast, call a customer service specialist for guidance.

### 4 Sides

- Double Face Ground Mount
- Single Face Overhead Mount

### 5 Border

- None MUTCD guidance - Borders are optional, but if used, must be the same color as the letters.
- Edge - Should use on dark backgrounds
- Inset - Should use on white backgrounds

### 6 a. Logo or Route Symbol

- None MUTCD guidance - Route symbols or Logos may be placed on the left side of a sign. The maximum height is the same as the letter height.
- Yes

### 6 b. Prefix/Suffix

- Full Size MUTCD Guidance - Prefix/Suffix Height may be smaller than the height of the primary copy and may be abbreviated. No punctuation is to be used.
- Half Size

### 7 Vandal Resistant Hole Punch

- None  VPA 12 Bolt thru
- Other

## Roadway Type Local Two Lane Roads 0-25 MPH

MUTCD guidance - Initial upper-case letters at least 4" high and lower-case letters 3/4 height of upper-case.

### 8 Dimensions

**Maple St**  Blade Height: 6" | Corner Radius .75"  
Letter Height: 4" | Prefix/Suffix Height: 2"  
Font: Highway Gothic B | Case: U/L

**Hickory Ln**  Blade Height: 8" | Corner Radius .75"  
Letter Height: 4" | Prefix/Suffix Height: 2"  
Font: Highway Gothic B | Case: U/L

## Two Lane Roads Over 25 MPH and Multi Lane Roads 0-40 MPH

MUTCD guidance - Initial upper-case letters at least 6" high and lower-case letters 3/4 height of upper-case.

**Second St**  Blade Height: 9" | Corner Radius .75"  
Letter Height: 6" | Prefix/Suffix Height: 3"  
Font: Highway Gothic B | Case: U/L

**Seventh St**  Blade Height: 12" | Corner Radius 1.5"  
Letter Height: 6" | Prefix/Suffix Height: 3"  
Font: Highway Gothic B | Case: U/L

## Multi Lane Roads Over 40 MPH

MUTCD guidance - Initial upper-case letters at least 8" high and lower-case letters 3/4 height of upper-case.

**Cherry Rd**  Blade Height: 12" | Corner Radius 1.5"  
Letter Height: 8" | Prefix/Suffix Height: 4"  
Font: Highway Gothic B | Case: U/L

## Overhead Mast Arm

MUTCD guidance - Initial upper-case letters at least 12" high and lower-case letters 3/4 height of upper-case.

**Custom Dr**  Blade Height: 18" | Corner Radius 1.5"  
Letter Height: 8" | Prefix/Suffix Height: 8"  
Font: Highway Gothic C | Case: U/L

**E Tombigbee St**  Blade Height: 18" | Corner Radius 1.5"  
Letter Height: 8" | Prefix/Suffix Height: 4"  
Font: Highway Gothic C | Case: U/L

**Holly Ct**  Blade Height: 24" | Corner Radius 1.5"  
Letter Height: 12" | Prefix/Suffix Height: 12"  
Font: Highway Gothic C | Case: U/L

**51 Terry Rd**  Blade Height: 24" | Corner Radius 1.5"  
Letter Height: 12" | Prefix/Suffix Height: 6"  
Logo/Route Symbol Height: 12"  
Font: Highway Gothic C | Case: U/L

Priced based on Length. Please e-mail or fax your list of signs, along with the specifications you've selected for a personalized quotation.

Street Name Signs **MUST** be  
Type II copy on Type I background or better.

We recommend using

**3M** High Intensity Prismatic for **Ground Mounted SNS**  
and

**3M** Diamond Grade Cubed for **Overhead Mounted SNS**

Distributed by: